Package: substackR (via r-universe)

October 11, 2026

Type Package

Title Access Substack Data via API

Version 0.0.9

Maintainer Jason R. <info@posocap.com>

Description Fetch latest, top, search or single posts from a Substack publication.

License MIT + file LICENSE

URL https://github.com/posocap/substackR

BugReports https://github.com/posocap/substackR/issues

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

Config/testthat/edition 3

VignetteBuilder knitr

Imports cli, httr2, rlang

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

Config/pak/sysreqs libssl-dev

Repository https://posocap.r-universe.dev

Date/Publication 2025-06-08 01:20:27 UTC

RemoteUrl https://github.com/posocap/substackr

RemoteRef HEAD

RemoteSha 432ccb27bb1cf66bdcc645b9a30cd9f53fc1c865

Contents

get_substack_latest 2
get_substack_post 2
get_substack_search 3
get_substack_top 3
set_substack_key 4

Index **5**

`get_substack_latest` *Latest Posts*

Description

Fetch the latest posts from a Substack publication.

Usage

```
get_substack_latest(publication_url, limit = 10L, offset = 0L)
```

Arguments

`publication_url`	Character, e.g. `"example.substack.com"`.
`limit`	Integer `[1-50]`, default `10`.
`offset`	Integer `>= 0`, default `0`.

Value

A `data.frame` (possibly zero-row) of post records.

`get_substack_post` *Get Single Post*

Description

Fetch a single post by its slug. Returns a one-row `data.frame`, or zero-row if not found.

Usage

```
get_substack_post(publication_url, slug)
```

Arguments

`publication_url`	Character.
`slug`	Character. Post slug.

Value

A `data.frame` with one row (or zero rows if missing).

get_substack_search *Search Posts*

Description

Search posts in a Substack publication. If zero results, returns an empty data.frame.

Usage

```
get_substack_search(publication_url, query, limit = 10L, offset = 0L)
```

Arguments

publication_url	Character, e.g. "example.substack.com".
query	Character. Search term.
limit	Integer [1–50], default 10.
offset	Integer >= 0, default 0.

Value

A data.frame (possibly zero-row).

get_substack_top *Top Posts*

Description

Fetch the most popular posts from a Substack publication.

Usage

```
get_substack_top(publication_url, limit = 10L, offset = 0L)
```

Arguments

publication_url	Character, e.g. "example.substack.com".
limit	Integer [1–50], default 10.
offset	Integer >= 0, default 0.

Value

A data.frame (possibly zero-row) of post records.

`set_substack_key` *Set your Substack API Key*

Description

Store your key once per session. Subsequent calls to other functions will use this key automatically.

Usage

```
set_substack_key(key)
```

Arguments

`key`	A single string: your Substack API key.

Value

Invisibly `TRUE` if successful.

Index

get_substack_latest, 2
get_substack_post, 2
get_substack_search, 3
get_substack_top, 3

set_substack_key, 4